



JSETS

Joint SARSAT Electronic Tracking System

SAR Controllers Training 2013
19 – 21 March 2013

SAM BAKER
SCIENCE SYSTEMS & APPLICATIONS INC.
CHIEF USMCC





Contact Information

- Database login
<https://prmsglobal.prms.af.mil>
- Operations Support Team
 - Commercial Phone: 586-239-3701
 - Defense Switched Network (DSN)
Phone: 312-273-3701
- Email address:
prmsmail@jricp.osis.gov



JSETS Concept

- All 406 MHz beacons must be registered
- DoD developed their own registration database
 - to protect sensitive information (e.g., unit info.)
 - To provide tracking of beacons between units
- In initial concept, USMCC would identify JSETS beacons on the alert message based on special beacon coding

Types of Beacons included in JSETS



- US coded national use beacons allocated by NOAA to DOD special programs
- Off the shelf beacons used by the DOD which cannot be identified by USMCC based on beacon coding

When to access JSETS to process USMCC Alert messages



- Alert message says “See JSETS”
 - in Registration section (usually Owner name)
 - in Beacon Decode section
 - in Special Program Name for Off-the-Shelf (OTS) beacons (based on periodic/monthly list of JSETS beacon provided to the USMCC by RMS)
 - in the next line after Special Program Name. When this occurs, the Registration section may contain information for specific beacon (based on associated special program)
- Alert message for unregistered US coded beacon (if OTS beacon added to JSETS in current month)
- Beacon type is identified as National User
- If registration information is in doubt, look the beacon up in the JSETS



Other Considerations

- JSETS contains many Off-the-Shelf beacons (OTS)
- JSETS list provided to USMCC monthly (new OTS beacon will not be identified in alert messages right away)
- USMCC does not ensure the accuracy of information in JSETS
- When evaluating Registration information accuracy in IHDB, ensure that the appropriate database is being evaluated
- Beacons in JSETS may also be in RGDB (but information in the two databases may differ)
- Beacons identified as JSETS may not be registered in the JSETS database

ACCESS JSETS



- Access <https://prmsglobal.prms.af.mil> via a .mil domain and CAC.
- Click the bottom link - JSETS Beacon Lookup
- Scroll to the bottom of the next page.
- Enter the Full Beacon Hex ID
- For CSEL
 - Enter the Full Beacon Hex ID, or
 - enter the HHRID in the PRQ-7/CSEL box
 - Note: For CSEL Beacons do not enter both the Hex ID and HHRID
 - The result (using CSEL HHRID as sample) is the info below (test info in this case).
Includes IDs, unit, and 24/7 contact info.

Personnel Recovery Mission Software

NOTICE AND CONSENT LOG-ON BANNER

You are accessing a U.S. Government (USG) Information System (IS) that is provided for USG-authorized use only.

By using this IS (which includes any device attached to this IS), you consent to the following conditions:

- The USG routinely intercepts and monitors communications on this IS for purposes including, but not limited to, penetration testing, COMSEC monitoring, network operations and defense, personnel misconduct (PM), law enforcement (LE), and counterintelligence (CI) investigations.
- At any time, the USG may inspect and seize data stored on this IS.
- Communications using, or data stored on, this IS are not private, are subject to routine monitoring, interception, and search, and may be disclosed or used for any USG authorized purpose.
- This IS includes security measures (e.g., authentication and access controls) to protect USG interests--not for your personal benefit or privacy.
- Notwithstanding the above, using this IS does not constitute consent to PM, LE or CI investigative searching or monitoring of the content of privileged communications, or work product, related to personal representation or services by attorneys, psychotherapists, or clergy, and their assistants. Such communications and work product are private and confidential. See User Agreement for details.

[Continue](#)

FOR OFFICIAL USE ONLY - PRIVACY SENSITIVE

PRMS *Personnel Recovery Mission Software*

[FAQ](#) [Contact Us](#)



Please choose your login below

[Register/Setup CAC](#)

[PRMS CAC Login](#)

This site is compatible with Internet Explorer 6.0, 7.0, and 8.0.

[PRMS Isoprep and EPA Computer Based Training V2.1.5](#)

[JSETS Beacon Lookup](#)

JSETS Beacon Lookup

For PRC-149's and ACRPLBs: Be sure to Break Beacon ID in **Four - Five** and then **Six** digits, e.g. 2DD7 XXXX F81FE0

For URT-140's: Be sure to Break Beacon ID in **Six - Seven** and then **Two** digits, e.g. ADCC07 XXXXXX 55

For PRQ-7's CSEL - the C/S ID is the **HHR ID Radio ID**

Only enter ONE beacon number for each search.

500-27-07MB	2DD01	<input type="text"/>	F81FE0
ACR PLB	2DD7	<input type="text"/>	F81FE0
ACR PLB-375	2DCE	<input type="text"/>	FFBFF
ACR TERRAFIX	2DCE4E	<input type="text"/>	FFBFF
ACR TERRAFIX (Var. 1)	2DC	<input type="text"/>	FFBFF
ACRPLB-300	2DCE5F	<input type="text"/>	FFBFF
ACRPLB-300 V1	2DF	<input type="text"/>	F81FE0
ACRPLB-300 V2	2DD7	<input type="text"/>	F81FE0
ACRPLB-300 V3	2DC	<input type="text"/>	FFBFF
ACRPLB-300 V4	2DD6	<input type="text"/>	F81FE0
ACRPLB-350B	2DCE	<input type="text"/>	FFBFF
ADT 406 ELT	ADCC5	<input type="text"/>	0020D
ADT 406S	ADCC4	<input type="text"/>	00265
AEROFIX 406 GPS I P-ELT	2DC	<input type="text"/>	FFBFF
AK-451 ELT	AE2C4	<input type="text"/>	002CD
Artex 110-406	2DC75	<input type="text"/>	FFBFF
ARTEX AVN/FI T V1	ADCC05	<input type="text"/>	40404

KANNAD 406-AF ELT V5 ADC6 5DD1
KANNAD 406-AF ELT V6 ADC6 E361
KANNAD 406-AF ELT V7 ADC6 B6E1
KANNAD 406-AF ELT V8 ADC6 8741
KANNAD 406-AF ELT V9 ADC6 CEE1
MBT 040600 2DD6 F81FE0
McMurdo E5 Smartfind ADC 0028D
McMurdo G5 Smartfind 2DC FFBFF
MOOG 406 ADCC01 40401
MOOG ELT ADCC01 40459
PRC-112G 2DD F81FE0
PRC-149/149A 2DD7 F81FE0
PRQ-7 CSEL
SEI PLB 2DD7 F81FE0
SRB-406 ADCC4 00215
SRB-406 V1 ADCC07 40401
URT-140 ADCC07 55
URT-44 2DD F81FE0
URT-44 V1 2DF F81FE0
URT-45 2A4F FBFF

Manufacturer's Serial Number

Full Beacon Hex

Search

Clear

Cancel