<u>The National Fire Codes Subscription Service - NFPA 10: Standard for Portable Fire Extinguishers, 2022</u> Edition

- Chapter 7 Inspection, Maintenance, and Recharging
- Chapter 8 Hydrostatic Testing
- Annex A Explanatory Material
- Annex B Recommended Markings to Indicate Extinguisher Suitability According to Class of Fire
- Annex C Fire Extinguisher Selection
- Annex D Operation and Use
- Annex E Distribution
- Annex F Selection of Residential Fire-Extinguishing Equipment
- Annex G Extinguisher Classification and Rating System
- Annex H Conditions of Selection
- Annex I Maintenance Procedures
- Annex J Typical Specification of Equipment Capable of Producing Dry Air
- Annex K Informational References

Code Links

Submit a Public Input >

Receive email alerts about this document ▶

My Alerts >

NFPA 10: Standard for Portable Fire Extinguishers, 2022 Edition - Chapter 6 Installation

not being used.

6.1.3 Placement.

6.1.3.1

Fire extinguishers shall be conspicuously located where they are readily accessible and immediately available in the event of fire.

6135

Fire extinguishers shall be located along normal paths of travel, including exits from areas.

6.1.3.3 Visibility.

6.1.3.3.1

Fire extinguishers shall be installed in locations where they are visible except as permitted by 6.1.3.3.2 or 6.1.3.3.3.

6.1.3.3.2 *

In rooms and in locations where visual obstructions cannot be avoided, signs or other means shall be provided to indicate the extinguisher location.

6.1.3.3.3

Fire extinguishers shall be permitted to be installed in fire extinguisher cabinets provided the extinguisher is visible or signs or other means are provided to indicate the extinguisher location.

6.1.3.3.4

Where signs or other means are used to indicate fire extinguisher location they shall be located in close proximity to the extinguisher.

6.1.3.3.5

Where signs or other means are used to indicate fire extinguisher location they shall be visible from the normal path of travel.

6.1.3.4 *

Portable fire extinguishers other than wheeled extinguishers shall be installed using any of the following means:

- (1)* Securely on a hanger intended for the extinguisher
- (2) In a bracket incorporating releasing straps or bands supplied by the extinguisher manufacturer
- (3) In a listed bracket incorporating releasing straps or bands approved for such purpose
- (4) In approved cabinets or wall recesses

6.1.3.4.1

Hangers and brackets shall not be fabricated in the field.