

TUGSAFE INTERNATIONAL ADDENDUM

Guidelines for Inspected Towing Vessels Under 300 GRT

Date:		

This job aid provides guidance for applicability of international conventions on towing vessels required to comply with 46 CFR Subchapter M that operate internationally. Requirements are based on length, build date and a tonnage measurement system. NVIC 11-93 Change 3 provides Coast Guard guidance on applicability of tonnage measurement systems.

Vessel Name:	Official Number:				
Overall Length: Less than 79 feet. Convention Length: Less than	n 79 feet. Assigned GRT tonnage: Less than 300.				
Certificates					
Requirement	Applicability	Cite			
Int'l Load Line Certificate (ILLC)	1	46 CFR Part 42 and ILLC Article 16			
Marpol Annex IV Statement of Voluntary Compliance	2,4	NVIC 01-09 (Guidance)			
Int'l Ballast Water Management Statement of Voluntary Compliance	3,4	CVC Policy 17-05 (Guidance)			
Equipment and Document Spot-Checks					
Requirement	Applicability	Cite			
Vessel equipped and in complance with applicable certificates.	All	N/A			
1 Only and in the transport built before Lebe 21 1000 that are \$ 150 CDT					

- 1. Only applicable to vessels built before July 21, 1968 that are \geq 150 GRT.
- 2. Applies to all vessels that carry >15 persons (passengers and crew).
- 3. Applies to vessels designed or constructed to carry ballast water.
- 4. Although not mandatory and administered through a voluntary program, vessel owners who operate on international routes are encouraged to participate.

Developed by the United States Coast Guard Towing Vessel National Center of Expertise.